BoilerMag®
Ultimate Heating System Protection

NEW!

BoilerMag X
Ultimate Heating System Protection

BoilerMag XL®
Ultimate Heating System Protection

Magnetic Performance: 4,000 Gauss Patented MicroMag style core	Magnetic Performance: 4,000 Gauss Patented MicroMag style core	Magnetic Performance: 4,000 Gauss Patented MicroMag style core
Pressure: 43 psi (3 Bar)	Pressure: 174 psi (12 Bar) 145 psi (10 Bar) if using AAV	Pressure: 174 psi (12 Bar) 145 psi (10 Bar) if using AAV
Pressure Drop: 2.4 psi at 11 gpm	Pressure Drop: 0.3 psi	Pressure Drop: 0.1 psi
Max Flow Rate: 14 gpm ($3m^3/h$)	Max Flow Rate: 18 gpm ($4m^3/h$)	Max Flow Rate: 28 gpm ($6m^3/h$)
Collection Capacity: 0.9 lbs (400 g)	Collection Capacity: 1.1 lbs (500 g)	Collection Capacity: 2.2 lbs (1 kg)
Temperature: 212°F (100°C)	Temperature: 212°F (100°C)	Temperature: 212°F (100°C)
Inlet/Outlet: 1" NPT (1-1/4" NPT adaptors included in kit) or 1" Press connections	Inlet/Outlet: 1-1/4" NPT	Inlet/Outlet: 1-1/2" NPT
Includes: Automatic Air Vent (AAV)	Includes: Automatic Air Vent (AAV)	Includes: Automatic Air Vent (AAV)